

ALTERNATIVE CAPACITY TRANSPORTATION SOLUTION

CORRcrate

VICTORY PACKAGING'S CORRCRATE
PROVIDES AN ECONOMICAL
ALTERNATIVE TO WOODEN LIFT VANS.

- Half the weight of wood, yet equally as strong
- Easy one-person assembly
- Totally waterproof when used with a CORR-shroud
- Easy storage, with 5 CORRCrates occupying the same space as one wood lift van
- 100% recyclable corrugated product
- Heat treated pallet



victorypackaging.com

©WestRock Company. Victory Packaging and the Victory Packaging Logo are trademarks owned by WestRock Company. All rights reserved.



**Victory
Packaging**
A WestRock Company

WHY TAKE THE CHANCE?

Restrictions for overseas shipments of wood containers and custom built packages to many countries are becoming more stringent. Importation of certain wood products into the U.S. and Canada is also becoming more regulated...why take any chances with your customer's goods...choose CORRcrate now!

THE CORRCRATE SEA CONTAINER CONSISTS OF THE FOLLOWING:

CAP:

Specific DIE CUT DESIGN for ease in K/D Transportation (Nests onto bottom cap)

- Doublewall strength EXCEEDS 400 lbs
- ECT Grade Board Strength 61
- AA Flute
- 62 lb KRAFT OUTSIDE LINER - 30 lb High Humidity Medium • 33 lb Inner Liner • 30 lb High Humidity Medium • 33 lb Strength Innermost Liner
- WATER RESISTANT ADHESIVES used in joining Liners / Mediums

WALLS:

Container consists of TWO IDENTICAL SIDE WALLS which overlap on two sides producing a double layer of Triplewall protection in opposite corners

- Specific design for easy knockdown transportation prevents crushing
- Triplewall construction EXCEEDS 900 lb Specifications
- ECT Grade Board Strength rated 80 by Manufacturer
- CAA Flute PUNCTURE RESISTANCE and STACKING STRENGTH
- 57 lb Kraft Outside Liner • 26 lb High Humidity Liner • 42 lb Inner Liner • 26 lb HH Med • 42 lb Inner Liner • 26 lb HH Med • 57 lb Strength Innermost Liner
- WATER RESISTANT ADHESIVE used again in joining Liners / Medium

BOTTOM:

Special DIE CUT DESIGN Identical to CAP

- Unique TUCK IN END design ELIMINATES need for Velcro, Tape, Staples to secure pallet to unit

PALLET:

- 87" x 42"

SHROUD:

WATERPROOF your CORRcrate utilizing our 6 MIL CLEAR SHRINK SHROUDS

- Shrouds Measure: 92" x 49" x 115"
- Use Standard Heat Shrink Gun to secure firmly
- Can be used as a loose cap by placing over container and cutting off excess plastic at bottom
- Order Shrouds separately

SIZE:

- Inside Dimensions: 86.5" x 44" x 79.75" (LxWxH)
- Usable Space: 175 Cubic Feet
- Outside Dimensions: 89.5" x 47" x 84.5"
- Outside Cube: 205 Cubic Feet
- Container TARE WEIGHT: Approximately 162 lbs

Knockdown Size: 89.5" x 47" x 17" (PALLET INSIDE)

